




LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

PTFE-isoliertes, doppelt verdichtetes IEC-Thermoelement mit freiliegender Sperrstelle und Miniaturstecker - Typen K, J, T



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Thermoelement Typ K, J oder T. Schnell ansprechende, geschweifte, freiliegende Verbindungsstelle, erhltlich in der Kabelspezifikation der Klasse 1 gem BS EN 60584-3:2008 mit einem Miniatursteckeranschluss.

Ideal fr Test- und Entwicklungsanwendungen.

Mssen Sie Ihren Temperatursensor kalibrieren?

Rckfhrbar auf ISO17025 (UKAS) Kalibrierstandards bietet Labfacility die Wahl zwischen einer 3- oder 5-Punkt-rckfhrbaren Kalibrierung mit unserer hauseigenen Kalibriereinrichtung, Sie knnen beliebige Temperaturpunkte zwischen -10 C und +200 C auswhlen.

Bitte beachten Sie, dass Sie bezglich der Lieferinformationen kontaktiert werden, wenn Sie Ihrer Bestellung eine Kalibrierungsoption hinzufgen.

Specifications

General Description	Fast response, welded exposed junction
Sensor Type	Exposed Junction
Thermocouple Type	K, J & T
Cable Length	300mm, 1, 2, 5 & 10m
Cable Type	Teflon® PTFE insulated twin-twisted lead
Core / Strands	1/0.2mm
Termination Type	Miniature flat pin plug colour coded in accordance IEC 584 or bare tails
Max. Temperature	+260°C
Min. Temperature	-75°C
Tolerance	Class 1
Standards Met	IEC-584-3
Connector Type	Plug
Connector Size	Miniature