



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

**Typ K 1/0.711
Hochtemperatur-Glasfaser-Doppelpverdrilltes
Glasfaser-Thermoelementkabel / -draht (ANSI)**



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Der Preis gilt fr 100M Lnge

Leistungsbeschreibung

Specifications

Product Code	XE-2812-100
General Description	Cores Twisted Together, 1/0.711mm Conductor Wire Size
Cable Length	100 metres
Cable Type	Fibreglass insulated twisted pair - High temperature
Core / Strands	2
Conductor Cross Section (mm²)	0.397
Outer Colour	n/a
+ Colour	Yellow
- Colour	Red
Insulation Material	Fibreglass - High Temperature
Loop Resistance (Ohms per combined metre)	2.5
Max. Temperature	+700°C
Min. Temperature	0°C
Number of Wires	3
Overall Jacket Insulation	No
Overbraiding	No
Screen	No



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

Standards Met	ANSI MC96.1 / wire tolerance: IEC 60584:1
Thermocouple Type	K (Nickel Chromium/Nickel Aluminium)
Tolerance	Class 1